



lampade alogene bispina UV-STOP Long life

bispina rinforzate G4

*Conforme alla CEI EN 60061-1 foglio n. 7004-59-6



PIN Ø 0,75 mm

bispina rinforzate GY6,35

*Conforme alla CEI EN 60061-1 foglio n. 7004-59-6



PIN Ø 1,25 mm

Durata 2.000 ore

UV-STOP



Volt	Watt	Attacco	Dim.	Luminosità lm	Codice	Classe energetica	Codice	Classe energetica
6	5	G4	9x30	50	420 2989	C		
	10	G4	9x30	100	420 2900	C		
	15	G4	9x30	230	420 2950	C		
12	10	G4	9x30	120	420 3010	C		
	20	G4	9x30	300	420 3015	C		
	35	G4	9x30	600	420 3020	C		
14*	20	G4	9x30	350	420 3018	C		
24	10	G4	9x30	100	420 3022	C		
	20	G4	9x30	350	420 3025	C		
28*	10	G4	9x30	140	420 3027	C		
	20	G4	9x30	350	420 3028	C		
6	50	G6,35	11x44	910			420 3042	C
12	75	GY6,35	11x44	1.500			420 3110	C
24	35	GY6,35	11x44	650			420 3120	C
	50	GY6,35	11x44	950			420 3125	C
	100	GY6,35	11x44	2.000			420 3135	C
	150	GY6,35	13x44	3.200			420 3140	C
	200	GY6,35	13x44	3.800			420 3142	D
	250	GY6,35	13x44	5.000			420 3145	D

*per uso nautico

SATINATE

Volt	Watt	Attacco	Dim.	Luminosità lm	Codice	Classe energetica	Codice	Classe energetica
12	10	G4	9x30	100	**420 3210	D		
	35	G4	9x30	535	**420 3220	D		
	20	G6,35	11x44	350			**420 3225	D
	50	G6,35	11x44	950			**420 3245	D

**Articoli in PHASE OUT, disponibili fino a esaurimento scorte.

Confezione 100 pz. Confezione mini con sovrapprezzo 20%. (Solo per prodotti a stock).